



KEMSONS
TELENETWORKING PVT. LTD.

CIN NO. U32109MH2019PTC332365

**WEATHERPROOF TELEPHONE IN FRP WITH ABS
KEYPAD.**



MODEL NO. KTPLWPFRPABS

Shop No.1B, Building No.6 & 7, Sector.5, Shanti Garden, Near St. Paul's High School.
Mira Road (E) Thane-401107 Contact: 7400404744 / 9082720528

Email: enquiries@kemsonstelenetworking.com
Web: www.kemsonstelenetworking.com



KEMSONS

TELENETWORKING PVT. LTD.

CIN NO. U32109MH2019PTC332365

KEMSONS Weatherproof Telephone Set is good in dusty environment conditions and is specifically made to work with contemporary communication networks. It is created under the supervision of our qualified personnel utilizing cutting-edge technology while keeping in mind the established industrial standards. Before delivery to our esteemed customers, our given telephone set is examined by a quality controller for compliance with various quality standards. The KEMSONS Weatherproof Telephone Set is renowned for its distinctive qualities, including immaculate finishing, weather resistance, and trustworthy functioning. This outdoor field call station is ideal for industrial applications since it is rated IP66, made of high-impact material, and equipped with an innovative telephone circuit and dynamic microphone and receiver to increase the signal to noise ratio.



MODEL NO:
KTPLWPFRPABS

Product Specification:

- **Phone Type:** Standard Analog.
- **Name:** WEATHERPROOF TELEPHONE IN FIBER REINFORCED PLASTIC WITH ABS KEYPAD.
- **KEYPAD.**
- **Model:** KTPLWPFRPABS
- **Dimensions:** L*W*H (225.50*177.50*72)in Millimeter(mm).
- **Voltage:** 24V-48V.
- **Power:** No external power except the telephone Line.
- **Dialing:** Pulse/Tone Dialing.
- **Ringer:** 95db @ 3meter.
- **Led indicator:** Red: For incoming call indication. Green: For telephone in-use indication.
- **Handset specification:** Passive Noise Cancelling Microphone and Receiver.
- **Keypad:** 16 KEYS (Push button Keypad)
 - A- Transfer Key.
 - B-Flash Key for 640ms Delay system.
 - C-Pause for in-between keys.
 - D- Redial.
- **Auto Cut:** Switchable Auto cut after 4mins (for wrongful placement of Handset on the cradle)
- **Cradle:** Magnetic (No moving parts)
- **Operating Temperature:** -30°C to +85°C
- **Mounting:** Wall/Desk Mount
- **Wiring:** 1 pair Telephone line from EPBX.
- **Materials:** Telephone Body- Fiber reinforced plastic. Cradle- Toughened ABS plastic. Keypad- Toughened ABS plastic. Handset- ABS with Steel Spiral cord.
- **Color:** Telephone Body-Grey Cradle-Black Ringer Module-Black Keypad- Black Handset-Black